Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1. (Currently Amended) A drum of a washing machine, comprising:

an opening confronting a door;

a rear wall provided opposite to the opening, the rear wall having a circumferential portion protruding more outward than a central portion; and

a circumferential wall between the opening and the rear wall; and

a spider attached to an outside of the rear wall, wherein the outside of the rear wall has a curved surface and the outside of the rear wall is in tight contact with a whole surface of the spider opposed to the outside of the rear wall.

- 2. (Canceled)
- 3. (Currently Amended) A drum assembly of a washing machine, comprising:

 a drum including a rear wall having a circumferential portion protruding more outward than a central portion;
 - a spider attached to an outside of the rear wall; and

a driving shaft connected to the spider, wherein the outside of the rear wall is in tight contact with a whole surface of the spider opposed to the outside of the rear wall.

- 4. (Original) The drum assembly as claimed in claim 3, wherein the circumferential portion and the central portion are connected to be slant.
- 5. (Original) The drum assembly as claimed in claim 3, wherein the rear wall is uniform in thickness.
 - 6. (Canceled)
- 7. (Original) The drum assembly as claimed in claim 3, wherein an edge part of the spider coupled with the circumferential portion of the rear wall is thinner than a central part of the spider connected to the driving shaft.
 - 8. (Currently Amended) A washing machine comprising:
 - a cabinet;
 - a tub in the cabinet;
- a drum including a rear wall having a circumferential portion protruding more outward than a central portion;

- a spider attached to an outside of the rear wall;
- a driving shaft connected to the spider; and
- a motor provided in the cabinet to be connected to the driving shaft, wherein the outside of the rear wall is in tight contact with a whole surface of the spider opposed to the outside of the rear wall.
- 9. (Original) The washing machine as claimed in claim 8, wherein the circumferential portion and the central portion are connected to be slant.
- 10. (Original) The washing machine as claimed in claim 8, wherein the rear wall is uniform in thickness.
 - 11. (Canceled)
- 12. (Original) The washing machine as claimed in claim 8, wherein an edge part of the spider coupled with the circumferential portion of the rear wall is thinner than a central part of the spider connected to the driving shaft.

13. (Original) The washing machine as claimed in claim 8, wherein a circumferential part of a rear side of the tub protrudes more outward than a central part of the rear side of the tub penetrated by the driving shaft.